

# PS series power supply

Enclosed, 12V DC switch mode power supply



CODE: **PS-401230** v1.0/IX  
TYPE: **PS 12V/3A enclosed switch mode power supply**

EN



## Features of the power supply unit:

- power output 3A/12÷15VDC\*
- wide AC input voltage range 85÷264V
- high efficiency 75%
- LED optical signalisation
- protections:
  - SCP short-circuit protection
  - overvoltage OVP
  - overvoltage protection
  - overload (OLP)
- warranty – 2 year from the production date



## DESCRIPTION

The power supply unit is intended for the feeding of alarm system equipments, which require 12V DC supply voltage and current load  $I=3A$ . The design enables simple changing of the output voltage, within the range of 12V÷15V DC, using a potentiometer. The power supply unit is protected against short-circuit, overload and overvoltage.

## TECHNICAL DATA

Supply voltage	85 ÷ 264 V AC, 120 ÷ 370 V DC
Current consumption	0,4A@230VAC max.
Supply power	40W max.
Efficiency	75%
Output current $t_{AMB}<30^{\circ}C$	3A - see graph 1.
Output current $t_{AMB}=40^{\circ}C$	2,1A - see graph 1.
Voltage adjustment range	12 V ÷ 15V DC
Ripple voltage	100mV p-p max.
Short-circuit protection SCP	electronic, automatic recovery
Overload protection OLP	105-150% of power supply, automatic recovery
Surge protection	varistors
Overvoltage protection OVP	>16V (automatic return)
Optical signalisation	green LED – presence of DC voltage
Operation conditions	2-nd environmental class, temperature: -10 °C÷+40 °C relative humidity 20%...90%, without condensation
Dimensions	129 x 98 x 38 [mm]
Net/gross weight	0,40kg / 0,43kg
Protection class PN-EN 60950-1:2007	I (first) – requires a protective conductor (PE)
Connectors	power-supply: $\Phi 0,63-2,50$ (AWG 22-10) outputs: $\Phi 0,63-2,50$ (AWG 22-10)
Declarations, warranty	CE, RoHS, 2 year from the production date

\* In order to extend the life of the power supply, the load current of 2,1A is recommended.

\* See graph 1.

